

PL62X



COFFEE MACHINE WITH L58E GROUP AND AUTOMATIC CONTROL OF THE EXTRACTION TEMPERATURE. THE PERFECT COFFEE AT THE RIGHT TEMPERATURE IN JUST 24 MINUTES, STABLE THERMAL EQUILIBRIUM WITH ANY COFFEE BLEND.

TECHNICAL FEATURES

L58E group with mechanical pre-infusion compatible with LELIT58 barista tools

Double probe HX System with thermosyphon circulation (Patent pending)

Silent pump

Temperature configuration button (Warm - Hot - Extra Hot)

Mode setting button (Xmode coffee or Xmode steam)

Steam boost

Stand-by function

Professional water-steam taps with spring closure

Machine ready and/or warming-up LED

Lack of water in the tank or no-tank LED

Active "Reserve mode"

I/O stainless steel back-lit switch

Double manometer for pump/steam pressure

Brushed stainless steel appliance body with cup warmer rack and drip tray with wire grate

Anti-burn multidirectional steam and hot water wands

Mug friendly

Boiler: 1.8 l with AISI316L stainless steel heat-exchanger

Water tank: 2.5 l

Dimensions LxDxH: 22x41x35 cm

Weight: 18.8 kg

DELIVERED WITH

LELIT58 2-ways filterholder with classic polished black handle and Coffee Slide spout

LELIT58 1 dose filter (9-11 g), IMS

LELIT58 2 doses filter (14-18 g), IMS

LELIT58 2 doses filter (18-21 g), IMS

LELIT58 blind filter, IMS

LELIT58 stainless steel tamper with red wooden handle

Spoon for coffee powder

Cup rack

35 l water softener filter

First cleaning kit

Small brush with nylon bristles

PL62X 230 V 50 Hz | Plug Type E+F

PL62X-AUS 240 V 50 Hz | Plug Type I

PL62X-AS 220 V 50/60 Hz | Plug Type G

PL62X-100 100 V 50/60 Hz | Plug Type B

PL62X-120 120 V 60 Hz | Plug Type B

